

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

Glued laminated timber (glulam) Block glued glulam

according to the product specification listed in the current addendum to this certificate placed on the market by

Company

HUTER & SÖHNE GMBH

Josef-Franz-Huter-Straße 31

AT-6020 Innsbruck

and produced in the manufacturing plant

AT-6020 Innsbruck, Josef-Franz-Huter-Straße 31

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14080:2013

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0631

Date of first issue: 23.07.2015

Date of issuance: 30.05.2022

This certificate will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforchung.at.



Dr. Andreas Neumüller
Authorised signatory



Dr. Manfred Brandstätter
Head of the Certification Body

Addendum to certificate 1359-CPR-0631

Date of issuance: 30.05.2022

Scope of certification:

GLUED LAMINATED TIMBER (GLULAM)

Timber species/ strength classes:	PCAB - spruce; ABAL - fir: GL 24h, GL 28h, GL 28c, GL30h, GL 30c, GL 32h, GL 32c LADC – larch: GL 24h, GL 28h, GL 28c, GL 30h, GL 30c PNSY – pine, PSMN – Douglasie: GL 24h
Mechanical resistance:	according to EN 14080
Service classes:	1, 2, 3
Adhesive:	
- Finger joints	Type I: MUF according to EN 301 I 90 FJ 0,1 M
- Surface bonding	Type I: MUF according to EN 301 I 90 GP 0,3 S
Reaction to fire:	D-s2, d0
Formaldehyde class:	E1
Natural durability class:	according to EN 350-2

BLOCK GLUED GLULAM

Timber species:	PCAB - spruce; ABAL – fir, LADC – larch
Cross-sectional shape:	rectangular
Adhesive – block joint:	Type I: MUF according to EN 301 I 90 GF 1,5 M